

COMPONENT

Clip with gripper

Grid clip with integrated gripper: the cable is adjusted directly from the profile.



TECHNICAL DATA

Cable range	Ø1.2 – 2.0 mm
Body	Ø10 × 32 mm
Thread / fixing	Base 35 × 54 mm
Material	Brass
Finishes	Nickel (NI) · black (BK) · white (WH)
Working load	14 – 37 kg
Safety factor	5:1

INSTALLATION

1

Snap the clip onto the flange of the T grid profile.

2

Check that it is centred and fully seated.

3

Hang the cable or accessory. Do not exceed the grid load.

ORDER CODE

DS-T-G-NI/BK/WH

NI nickel · BK black · WH white

Part of: DS-T-24

WORKING LOAD PER CABLE

CABLE	GALVANISED	STAINLESS AISI 304
Ø1.2 mm	14 kg	13 kg
Ø1.5 mm	21 kg	20 kg
Ø2.0 mm	37 kg	34 kg

Static load with a 5:1 safety factor, based on 60 % of the cable break load (gripper efficiency). Theoretical values until laboratory validation.

DSUSPEND LABORATORY TESTS

Tensile test to failure	☐ PENDING
Slip under load	☐ PENDING
Salt spray ISO 9227	☐ PENDING
Adjustment cycles	☐ PENDING

SAFETY

 Static loads only	 No chlorine or corrosive areas	 No grease or lubricants
 Never use frayed cable	 Maximum 60° inclination	 Do not paint components

Provisional document: data will be completed with our laboratory tests. Images for reference only. Data subject to change without notice.